

WALL PROTECT SALT STOP

Prevents salt deposits on your wall



Product description

WALL PROTECT SALT STOP is a salt neutraliser which causes the salts to crystallise inside the bricks and thus not collect on the surface. As a result, these salts cannot affect the appearance of the masonry. It also protects adhesion with any (waterproof) filler.

Application

For use on porous interior and exterior masonry such as concrete and terracotta or sand-lime brick.

Advantages

- › Prevents efflorescence
- › Ideal primer for wall products
- › Reduces transfers of moisture

How much product do I need?

- Approx. 0,1 - 0,25 L / m²

Handy tips?

- Store in cool (max 25°C) dark place.
- Do not apply at temperatures below 0°C.
- Shelf life: at least 12 months. Limited shelf life once opened.
- Clean your tools with water.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Silicate	Transparent	1 L / 5 L	Approx. 0,1 - 0,25 L / m ²	About 4 - 24 u	n/a	Yes

WALL PROTECT SALT STOP

Prevents salt deposits on your wall



INSTRUCTIONS

What do I need?



How do I prepare the surface?

- The substrate must be free of grease and loose particles. Brush off salt efflorescence before applying
- Treat any green mould, lichens and algae with **GARDEN CLEAN GREEN REMOVER**.

How do I use the product?

- Apply one or more layers using brush or pressure sprayer as appropriate.
- During application and while the product is drying, the temperature should not drop below 0°C.
- After 4 hours drying, further application of cement-bonded materials is possible. At least 24 hours drying should be allowed before applying acrylic or silicate paints.
- Some salts may still appear on the surface during the drying process. You can simply brush these off.



Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

